

# MICROFLEX®

## ▲ FREEFORM® SE



BLUE  
 NITRILE  
 NON-STERILE  
 AMBIDEXTROUS  
 TEXTURED FINGERS  
 BEADED CUFF  
 FOR SINGLE USE ONLY  
 NON-LATEX

### POWDER-FREE EXAMINATION GLOVES

If your light to mid-duty tasks demand reliable protection, FreeForm® SE is the glove you need. The unique combination of strength and comfort makes FreeForm® SE gloves a top choice for a variety of jobs.

- Best for light to mid-duty tasks that need reliable protection
- Non-stick properties resists tape and adhesives
- Textured fingertips for enhanced grip



### STRONG YET COMFORTABLE FOR EXTENDED USE

PRODUCT CODE		PACKAGING	
XS	FFS-700-XS	100	Gloves/Box
S	FFS-700-S	10	Boxes/Case
M	FFS-700-M		
L	FFS-700-L		
XL	FFS-700-XL		

GLOVE PROFILE		ASTM D 6319	FREEFORM® SE
Length	mm (inches)	min. 220 (8.7)	243 (9.6)
Cuff Thickness	mm (mils)	n/a	0.07 (2.8)
Palm Thickness	mm (mils)	min. 0.05 (2.0)	0.09 (3.5)
Finger Thickness	mm (mils)	min. 0.05 (2.0)	0.13 (5.1)
Tensile Strength	Before Aging	min. 14	32
	After Aging	min. 14	31
Elasticity/Elongation	Before Aging	min. 500	500
	After Aging	min. 400	400
Pinhole Defect Rate*	(AQL)	max. 2.5	1.5

\* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED INDUSTRIES